

**Attachment "B"**  
Clean Copy of Amended Claims)

1. (Thrice Amended) A seatback for an automobile comprising:

a seatback frame comprising:

side frames spaced apart from each other;

C1 a headrest member supported by the seatback frame and rotatable relative to the side frames about a pivot,

the headrest member comprising:

a headrest mounted on the seatback frame; and

a supporting member including a pressure receiving portion, the supporting member being disposed between the side frames and supporting the headrest; and

wherein the seatback frame comprises a cross frame disposed between the side frames and in front of the supporting member for stopping the headrest member from pivotal motion.

C2 E1 cont 4. (Twice Amended) A seatback according to claim 1, wherein the supporting member comprises:  
a holder fitted with the headrest; and  
a supporting member body fixed with the holder and the pressure receiving portion.

C3 6. (Twice Amended) A seatback according to claim 1, further

C1  
C2 comprising:

a biasing means fixed between the side frames for biasing forwardly the pressure receiving portion.

C3  
C4  
7. (Twice Amended) A seatback according to claim 6, wherein the pressure receiving portion is covered with a cover made of a synthetic resin, and the cover has a hook engaged with the biasing means.

C4  
14. (Twice Amended) A seatback according to claim 1, wherein the cross frame is bridged between upper ends of the side frames.

15. (Thrice Amended) A seatback for an automobile comprising:

C5  
a seatback frame including:

a side frame;

a headrest supported by the seatback frame and rotatable relative to the side frame about a pivot; and

a stopper fixed to the side frame and disposed in front of the headrest for stopping the headrest from pivotal motion.

C6  
16. (Twice Amended) A seatback according to claim 15, wherein the headrest includes:

C6  
cont E1  
W17

a supporting member supporting a seat pillow;  
a pressure receiving member extending from the  
supporting member; and

wherein the pivot is between the supporting member and the  
pressure receiving member, and the pivot is supported to the  
seatback frame for rotatably supporting the supporting member.

c7

18. (Twice Amended) A seatback according to claim 16,  
wherein the stopper includes a first stopper extending  
longitudinally relative to the pressure receiving member for  
stopping the pressure receiving member from rearward pivotal  
motion.

19. (Twice Amended) A seatback according to claim 16,  
wherein the stopper includes a second stopper extending  
transversely relative to the supporting member for stopping the  
supporting member from frontward pivotal motion.

20. (Twice Amended) A seatback according to claim 16,  
further comprising:  
a resilient member biasing the pressure receiving member to  
an original position.

21. (Twice Amended) A seatback according to claim 20,

*C1*  
*omit*  
wherein the resilient member includes a spring bridged  
between side frames.

*C2*  
*cont*  
22. (Twice Amended) A seatback according to claim 16,  
further comprising:  
a cover covering an end of the pressure receiving member.

*C8*  
24. (Twice Amended) A seatback according to claim 22,  
wherein the cover has a hook, and a resilient member is  
engaged with the hook for biasing the pressure receiving member  
to an original position.

25. (Twice Amended) A seatback according to claim 16,  
wherein the pressure receiving member includes a flat end.

*C9*  
28. (Twice Amended) A seatback according to claim 16,  
wherein the supporting member further comprises:  
a holder for fitting the seat pillow therein.